

EtonGreen™

One Goal. One Passion-Etongreen

Customer Care
+91 81282 95219



PRODUCTS

- SOLAR WATER HEATER
- SOLAR ROOF TOP
- SOLAR STREET LIGHT
- HEAT PUMP



વિજળી અને
પૈસાની બચત



મેઇન્ટેનન્સ ફી



ઉચ્ચ કાર્યક્ષમતા



દિવસ ગરમ
પાણીની ગેરંટી

TECHNICAL SPECIFICATION OF TANK

Inner Tank	: 2.5 mm Galvanised
Inner Coating	: Marine Paint / EPOXY Coating
Outer Cover	: 0.50 mm Galvanised (G.I. And PP Powder Coating)
Insulation	: 50 mm Puf
Stand	: 1.6 mm (GI) PP Powder Coating
Connection	: 1" (Inlet And Outlet)
Ele. Backup Provision	: 1.25"
Boalting	: S.S Nuts And Bolt

TECHNICAL SPECIFICATION OF TUBE

Material	: 1.6 Borosilicate Glass 3.3,
Dimension	: Outer Dia - 58 mm : Inner Dia - 47 mm : Lengh - 1800 mm / 2100 mm
Abs. Coating Graded	: CU-Au-N/SS (Three Layer)
Absorptance	: > 92% (AM 1.5)
Emittance	: < 8% (80 °C)
Vacume	: $P < 5 \times 10^{-3}$ PA
Stgn.Temperature	: > 200 °C
Heat Loss	: < 0.8 W / 59 M
Max. Strength	: 0.8 mpa

DEALER :

For Dealership & Distributorship Inquiry
+91 99049 54348 / +91 93270 30734



AN ISO 14001 : 2004
CERTIFIED COMPANY



Follows On :
Etongreensolar



SIDDHIVINAYAK ENGINEERING COMPANY

Office : Anmol Park-A, Shop no 5, Plot No.5/1, Near Aji Dem
Chowkdi, Bhavnagar Road, Rajkot Gujarat India 360003.

Factory Address : Balaji Industrial GIDC, Plot No. 5, Rajkot.
E-mail : sales@etongreens.com, Web. : www.etongreens.com